

# JARRETT T SERIES SLASHERS\*

***"We chose Jarrett slashers for the maintenance of all spectator areas and car parks."***

— M. Easthope, Course Supervisor, Eastern Creek Raceway



The EHDT240 twin gearbox slasher, from rear



The EHDT240 twin gearbox slasher, from front

## General construction

- 5mm steel deck sheet
- 12mm steel reinforced gearbox plate (17mm total thickness for gearbox mounting)
- Obstruction free top deck (no debris collection points)
- Obstruction free cutting chamber
- Strong RHS linkage frame with clevis hitch and Cat 1/2 (HDT) or Cat 2 (EHDT) lifting pins
- Built-in front and rear discharge deflector plates
- Adjustable skids with top and side gussets

## Gearbox, driveshaft & clutch

- Quality Jarrett Australian-made gearboxes
- Quality Jarrett Australian-made 1:1 splitter box
- HDT: Gearbox speed ratio: 1:1.97
- HDT: Gearbox rating: 57 kw (75hp)
- HDT: Series 6 telescopic triangular shaft
- HDT: 2 friction plate 200mm clutch
- EHDT: Gearbox speed ratio: 1:1.95
- EHDT: Gearbox rating: 83kw (110hp)
- EHDT: Series 8 telescopic triangular shaft
- EHDT: 4 friction plate 200mm clutch
- Precision flexible solid rubber drive gearbox couplings

## Cutter disc

- Tapered splined hub
- Fabricated cutting disc for maximum strength and shock protection
- Spring steel Jarrett slasher blades:  
6 x 75x10mm step and twist (HDT)  
6 x 100x12mm step (EHDT)
- Jarrett 'taper lock' blade bolts

## Options

- Front and/or rear rubber deflector extension guards
- Chain guard set, front and/or rear
- Solid rubber, dual rear wheel kit (suit all models)
- Galvanised body

## Specifications

Model	Width	Weight	Gbox	Min pwr	Mount	Link	Cut height	Tip speed
HDT180	1.80 m	510 kg	75 hp	45 hp	Centre	Cat 1/2	10–85 mm	73.7 m/s (14,504 ft/min)
HDT210	2.10 m	560 kg	75 hp	55 hp	Centre	Cat 1/2	10–85 mm	88.0 m/s (17,325 ft/min)
HDT240	2.40 m	610 kg	75 hp	65 hp	Centre	Cat 1/2	10–85 mm	98.2 m/s (19,330 ft/min)
EHDT240	2.40 m	700 kg	110 hp	70 hp	Centre	Cat 2	10–85 mm	65.5 m/s (12,890 ft/min)
EHDT300	3.00 m	800 kg	110 hp	80 hp	Centre	Cat 2	10–85 mm	81.9 m/s (16,116 ft/min)
EHDT360	3.60 m	900 kg	110 hp	90 hp	Centre	Cat 2	10–85 mm	98.2 m/s (19,330 ft/min)



### Jarrett Implements Pty Ltd

(ABN 81 000 582 918)

244 New Line Road, DURAL NSW 2158 Australian tel: 02 9651 2166 fax: 02 9651 3069

International tel: +61 2 9651 2166 International fax: +61 2 9651 3069

Email: jarrett@acay.com.au

\* Due to continuous development, specifications may change without notice or obligation to upgrade superceded models.

Sold and serviced by: